

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in this application.

Listing of Claims:

- 1-22. (Canceled)
23. (Previously Presented) A method for cleaning a filtration system comprising:
- (a) removing liquid product from the filtration system and recovering at least a part of the liquid product;
 - (b) flooding the filtration system with a first aqueous media to remove at least a portion of solids in the filtration system;
 - (c) flushing the filtration system with a gaseous media to remove at least a portion of the first aqueous media;
 - (d) treating the filtration system with a multiple phase treatment composition comprising a gaseous phase and a liquid phase;
 - (e) soaking the filtration system for at least about 1 minute following the step of treating the filtration system with a multiple phase treatment composition;
 - (f) flooding the filtration system with a second aqueous media; and
 - (g) rinsing the filtration system.
24. (Original) A method according to claim 23, wherein the liquid product comprises a food product.
25. (Original) A process according to claim 23, wherein the liquid product comprises a dairy product.

26. (Original) A method according to claim 23, wherein the filtration system comprises a spiral wound membrane.
27. (Original) A method according to claim 23, wherein the step of removing liquid product comprises displacing the liquid product with water.
28. (Original) A method according to claim 23, wherein the first aqueous media comprises water.
29. (Original) A method according to claim 23, wherein the first aqueous media comprises an alkaline solution having a pH of between about 8 and about 13.
30. (Original) A method according to claim 23, wherein the step of flooding the filtration system with a first aqueous media comprises circulating the first aqueous media within the filtration system for at least about 10 minutes.
31. (Original) A method according to claim 23, wherein the step of flushing the filtration system with a gaseous media comprises flushing for less than about 5 minutes.
32. (Previously Presented) A method according to claim 23, wherein the step of treating with a multiple phase treatment composition comprises applying the multiple phase treatment composition for at least about 3 minutes.
- 33-34. (Canceled)
35. (Original) A method according to claim 23, wherein the step of flooding the filtration system with a second aqueous media comprises recirculating the second aqueous media for between about 5 minutes and about 15 minutes.

36. (Original) A method according to claim 23, wherein the second aqueous media comprises water having a temperature of between about 100°F and about 120°F.

37-41. (Canceled)